



TECHNICAL DATA SHEET

DR. SEAL NO MORE RUST

PRODUCT DESCRIPTION

Dr. Seal No More Rust is a clear liquid that is an effective solution for a rust-free surface. Formulated to end rust and prevents future rusting. Dr. Seal No More Rust counteract and convert rust into a black primer that join to the surface and make a waterproof guard that made long-term rust protection.

PRODUCT BENEFITS

- One easy step
- Can be applied to damp surfaces
- Long lasting (protect surfaces for years)
- Ready to Use
- Ideal for preparing surfaces prior to painting
- > Seal out moisture to prevent future rusting

TYPICAL APPLICATIONS

- Dissolves rust from rusted iron or steel
- Removes rust from tools, automobiles, machinery, pipe, conveyor, drums, boats, motorcycle, bridges, guard rails, lamp stands, on iron railings, roofing and spouting, gutters, outdoor fixtures, hinges, fences and gates, wrought iron, air conditioning and refrigeration units.

APPLICATION

For New Metal: Clean surface with mineral spirits or paint thinner to remove oil or grease. Apply No More Rust by brush or spray, allowing drying for 24 hours before applying succeeding coats.

For Rusted Metal: Remove loose materials using a wire brush or sandpaper. Apply No More Rust by brush or spray, allowing drying for 24 hours before applying succeeding coats.

PROLONGS LIFE OF IRON OBJECTS SUCH AS:

CALVANIED WON (6.1.3)

CALVA





COMPONENTS

H₃PO₄: 85.05
CL: 0.0001%
SO₄: 0.0018%
AS: 0.00002%
PB: 0.0003%
F: 0.00015%
H₃PO₃: 0.0028%

HEALTH & SAFETY

Avoid prolonged inhalation of vapors or contact with skin. Do not ingest. Wear protective gear, gloves and goggles when working with No More Rust. Consult MSDS for full list of hazards

STORAGE

Store in cool dry conditions and keep away from heat and open flame. Cross ventilation is a must. Keep out of reach of children.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

Address: 826 Zacateros St., Sta. Cruz Manila, Philippines), 1405

Tel: 733-3007/733-1183 Fax: 736-4589

E-mail: nccreus_richinnovation@yahoo.com richinnovation@globe.ap.blackberry.net