

**GUN A NAIL EXTRA** 

Page: 1

Compilation date: 13/10/11

Revision No: 2

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: GUN A NAIL EXTRA
Product code: SBGAN / SBGANC4

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

WEST YORKSHIRE

LS9OSW

**ENGLAND** 

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: pault@everbuild.co.uk

### 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; N: R51/53; -: R67

Most important adverse effects: Highly flammable. Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment. Vapours may cause drowsiness and dizziness.

Classification under CLP: This product has no classification under CLP.

#### 2.2. Label elements

Label elements under CHIP:

Hazard symbols: Highly flammable.

Dangerous for the environment.





Risk phrases: R11: Highly flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R67: Vapours may cause drowsiness and dizziness.

**GUN A NAIL EXTRA** 

Page: 2

Safety phrases: S2: Keep out of the reach of children.

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S51: Use only in well-ventilated areas.

S46: If swallowed, seek medical advice immediately and show this container or label.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT**: This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

### ETHYL METHYL KETONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

### NAPTHA (PETROLEUM) HYDROTREATED LIGHT

-	-	F: R11; Xi: R38; N: R51/53; Xn:	-	1-10%
		R65; -: R67		

## NAPTHA (PETROLEUM) HYDROTREATED HEAVY

-	64742-48-9	F: R11; Xi: R38; N: R51/53; Xn:	-	1-10%
		R65; -: R67		

#### **CYCLOHEXANE**

203-806-2	110-82-7	F: R11; Xi: R38; Xn: R65; -: R67;	Flam. Liq. 2: H225; Asp. Tox. 1: H304;	1-10%
		N: R50/53	Skin Irrit. 2: H315; STOT SE 3: H336;	
			Aquatic Chronic 1: H410; Aquatic	
			Acute 1: H400	

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

**GUN A NAIL EXTRA** 

Page: 3

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness

or mental confusion may occur.

#### 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. May form flammable / explosive

dust-air mixture.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Do not use equipment in clean-up procedure which may produce sparks.

#### 6.4. Reference to other sections

### Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

### **GUN A NAIL EXTRA**

Page: 4

Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these paramaters will dramatically reduce shelf life and invalidates all product warrenties.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

#### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

# Hazardous ingredients:

### ETHYL METHYL KETONE

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m3	899 mg/m3	-	-

#### **CYCLOHEXANE**

UK	350 mg/m3	1050 mg/m3	-	-
----	-----------	------------	---	---

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration

is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Paste

Colour: Beige

Odour: Pungent

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Boiling point/range°C: 64 Flash point°C: -10

Relative density: 1.20 VOC g/l: 30%

**GUN A NAIL EXTRA** 

Page: 5

#### 9.2. Other information

Other information: Not applicable.

### Section 10: Stability and reactivity

#### 10.1. Reactivity

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

Toxicity values: Not applicable.

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness

or mental confusion may occur.

## **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: Not applicable.

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

### 12.4. Mobility in soil

**GUN A NAIL EXTRA** 

Page: 6

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1133

## 14.2. UN proper shipping name

Shipping name: ADHESIVES

#### 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

### 14.6. Special precautions for user

**Tunnel code:** D/E **Transport category:** 3

### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

### **GUN A NAIL EXTRA**

Page: 7

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eve irritation.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

R11: Highly flammable. R36: Irritating to eyes.

R38: Irritating to skin.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.