

Tels. 733-3007; 733-7783 Fax: 736-4589

# TECHNICAL DATA SHEET KÖNIG ALL

#### **DESCRIPTION**

**KÖNIG ALL** is a polyvinyl acetate-based adhesive for use by paper and packaging industries as well as wood crafting, homes, schools and offices.

#### **FEATURES**

- . Provides superb adhesion to a variety of surfaces
- . Environment-friendly
- . Non-flammable & non-hazardous

#### **USAGE**

Apply with brush or roller. Spread adhesive in an even uniform manner in one of the substrate to be bonded. Press assemblies together immediately after application.



6 months to 1 year from date of production provided it is stored away from sunlight and with proper ventilation. Store in a cool, dry place.

## **PACKAGING**


Available in 130gms and 500 gms bottle packagings.

### MATERIAL SAFETY HANDLING INFORMATION

Konig All is non-hazardous. However, the usual precautions for handling chemicals must be observed. PRODUCT PROPERTIES

Properties	Test Method	Values
Appearance	Visual Milky	White
Viscosity @ 250 °C, cps (Spindle #4, 60 rpm)	ASTM D2196	3,500 – 5,500 cps
pH @ 25oC	ASTM D4584-86	4.0 - 6.0
Specific Gravity 25/25	ASTM D1963	$1.05 \pm 0.05$
% Non-Volatile , by wt	ASTM D2369-98	47.0 – 49.0
Calculated Tg, °C		
Mechanical Stability	In-house	Good
Heat Stability (60°C)	In-house	Good





Warehouse: 643 Mercedes Avenue, Pasig City