

H.Q.: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel: (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,

47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

X'traseal® x'bond CONSTRUCTION ADHESIVE

1. Product & Company Identification

1.1 Product Detail

Product name: x'bond Panel Adhesive

Physical form: Paste

Odour: Organic Solvent odour

CAS No.: Mixture

Flammability: Highly Flammable

1.2 Company Details:

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100

Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

Chemical Name	CAS No.	Approx WT%	
Synthetic Rubber			
Hexane	64742-49-0	10-30%	
Resin		10-30%	

Mineral fillers 30-60% Additives 1-10%

3. Hazards Identification

Ingestion: Harmful.

Skin contact: Uncured product contact will irritate lips, gums and tongue.

Uncured product contact may irritate the skin.

Inhalation: High vapour concentrations may cause irritation, headache and

dizziness. Toxicity data indicates inhalation of 5000ppm/10 minutes of nhexane can produce central nervous system

effects.

Eye contact: Uncured product contact irritates eyes.

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap. In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

Advice to doctor: Treat symptomatically.



H.Q.: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel: (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,

47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal x'bond CONSTRUCTION ADHESIVE

5. Fire Fighting Measures

Flammability: Highly flammable.
Suitable extinguishing media: Foam, CO2, dry power.

Unsuitable extinguishing media: Unknown

Hazardous decomposition: Oxides of carbon, light flammable hydrocarbons, smoke

and fumes.

6. Accidental release measures

Methods for cleaning up: take up mechanically.

7. Handling and Storage

Handling: Ensure good ventilation during processing. Wear safety

shoes.

Protection against fire/ explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

8. Exposure control/ Personal protection

Ingredients with limited values to be controlled: Hexane (n-hexane):TWA:50ppm

(176mg/m³)

Local exhaust: Recommended
General ventilation: Recommended

Hand protection:

Eye protection:

Suitable protective gloves.

Safety/ protective glasses.

9. Physical and Chemical Properties

Form: Paste Specific gravity: 1.16 Colour: Tan

Viscosity: 10,000 to 1,000,000 cps

Odour: Solvent Odour

Volatile % (25°C): 25-40% Solubility in water: Non

Boiling point: 62-68°C (Hexane)

Flash Point: -20°C
Ignition temperature: Non Known

Note: the above information is not intended for use in preparing specification.



H.Q.: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel: (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,

47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

X'traseal® x'bond CONSTRUCTION ADHESIVE

10. Stability and Reactivity

Chemical stability: Stable

Incompatibility (material to be avoid): Strong oxidizing agents, acids

Conditions to be avoid: Sources of ignition.

Dangerous reactions: Combustion.

Dangerous products of decomposition: Oxides of carbon, light flammable hydrocarbons,

smoke and fumes.

11. Toxicological Information

Acute toxicity: Harmful

Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Additional Toxicological information: Danger of serious damage to health by prolonged

exposure.

12. Ecological Information

Complete information not yet available.

13. Disposal Considerations

Shut off all possible sources of ignition. Clean-up personnel to wear appropriate personal protective equipment.

Please consult with the operator of the waste disposal facility for any further information. With respect to local regulation, dispose of to suitable incineration plant.



H.Q.: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel: (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,

47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

X'traseal® x'bond CONSTRUCTION ADHESIVE

14. Transport Info	rmation		
Proper shipping name: adhesives/sealants containing flammable liquid.			
Risk phrases:	R11	Highly flammable.	
	R20	Harmful by inhalation	
	R21	Harmful in contact with skin	
	R22	Harmful if swallowed	
	R48	Danger of serious damage to health by prolonged exposure.	
Safety phrases:	S9	Keep container in a well ventilated place.	
	S16	Keep away from sources of ignition- No Smoking.	
	S24/25	Avoid contact with skin and eyes.	
	S29	Do not empty into drains	
	S51	Use only in well ventilated areas.	

15. Regulatory Information

Complete information not yet available.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***