



PRODUCT DATA SHEET

ZAR® CLEAR WOOD SEALER

DESCRIPTION

ZAR Clear Wood Sealer is a non air-polluting clear wood treatment. Protects exterior wood surfaces from the damaging effects of rain, sun and other weather. It can be applied to new or old wood that has been left unstained and unpainted. Its unique formula is oil based but clean up is easy with soap and water.

USES

ZAR Clear Wood Sealer can be applied to new or old wood that has been left unstained and unpainted.

It is ideal for decks, rails, posts, fencing, wood siding, shingles, shakes and other exterior wood surfaces where a natural look is desired. This product can be used on new, unweathered pressure-treated lumber.

SURFACE PREP

New Wood: Remove all oil, grease, dust, dirt and loose wood fibers. All mildew must be removed with the following washing solution: 1 quart bleach, 2 tablespoons detergent, 6 tablespoons UGL MEX to 9 quarts of water. Apply with scrubbing brush, rinse thoroughly and allow to dry. ZAR Deck & Siding Cleaner can also be used according to manufacturer's instructions.

Weathered Wood: Use ZAR Deck & Siding Cleaner to restore the surface.

APPLICATION

Stir thoroughly before and during application. Apply when surface and air temperatures are greater than 50°F. Applying when temperatures are greater than 90°F or in direct sunlight can cause premature water evaporation, leading to poor penetration and/or lap marks. Under these conditions, dampen surface before application. Do not apply if rain is expected within 24 hours. Apply with synthetic brush, roller (short nap), spreading pad, or garden sprayer (keep dry brush available to brush out puddles). Avoid uneven application and surface puddles. Apply only one coat. Do not thin. Allow overnight drying before subjecting to traffic. Reapply when water stops beading or when wearing shows in high traffic areas on decks.

TECHNICAL DATA

% Non-Volatile by Weight - 8.0%
% Non-Volatile by Volume - 7.4%
Weight per gallon - 8.26 lbs
pH=8.7
Viscosity: 11SEC.Ford #4 cup at 25° C.

CLEAN-UP

Clean tools with soap and water immediately after use.

COVERAGE

300 square feet per gallon. On less porous woods coverage could be greater.

PRODUCT DATA
ZAR CLEAR WOOD SEALER

LR2/07



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com