

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ZAR DECK & SIDING STAIN – SEMI-TRANSPARENT – ALL COLORS
PRODUCT CODE: 0901, 0902, 0903, 0904, 0907, 0908, 0952, 0953, 0954

HMIS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: **UNITED GILSONITE LABORATORIES**
ADDRESS: **1396 JEFFERSON AVENUE
SCRANTON, PA 18509**

EMERGENCY PHONE: **(800) 424-9300**
INFORMATION PHONE: **(570) 344-1202**
NAME OF PREPARER: **R. BARAKO**

DATE ISSUED: JUNE 2006
SUPERSEDES: JANUARY 2006

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mmHg@TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
WATER	7732-18-5	NOT ESTAB	NOT ESTAB	NOT ESTAB	1.0 (68F)	60
*ETHYLENE GLYCOL MONO - BUTYL ETHER	111-76-2	25 PPM (SKIN)	25 PPM (SKIN)	5 PPM (NIOSH)	0.9 (77F)	6
MODIFIED OIL POLYMER	PROPRIETARY	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	20
CALCINED DIATOMACEOUS – EARTH	6855-54-9	5 MG/M ³	10 MG/M ³	NOT ESTAB	N/A	<5
WAX EMULSION	NOT ESTAB	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	<5

* Indicates toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of CFR 372
SEE SECTION IX FOR LIST OF ADDITIONAL INGREDIENTS

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 F

VAPOR DENSITY: HEAVIER THAN AIR

COATING V.O.C.: DOES NOT EXCEED MAXIMUM VOC 250 G/L (VOS 2.08 LB/GAL)

SOLUBILITY IN WATER: SOLUBLE

APPEARANCE AND ODOR: WHITE OR COLORS, PRODUCT SPECIFIC. TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O = 1): 1.0

EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINERS MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

METHOD USED: N/A

LOWER: 1.1% **UPPER:** 10.6%

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, HEADACHE, NAUSEA, MENTAL CONFUSION, SLURRED SPEECH DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC) NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? YES OSHA REGULATED? NO
TITANIUM DIOXIDE HAS BEEN CHARACTERIZED BY IARC AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) THROUGH INHALATION (NOT INGESTION). THIS CLASSIFICATION IS BASED UPON ANIMAL INHALATION STUDIES. EPIDEMIOLOGY STUDIES DO NOT SUGGEST AN INCREASED RISK OF CANCER IN HUMANS FROM OCCUPATIONAL EXPOSURE TO TITANIUM DIOXIDE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MTRIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATIO PERSISTS

INGESTION: GIVE ONE OR TWO GLASSES OF WATER. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS DO NOT GIVE ANYTHING BY MOUTH. CONSULT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVISE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BRATHING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATORS WITH SOLID PARTICULATE CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTIONS II & IX

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE CHEMICAL SPLASH GOGGLES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM. WASH COMTAMINATED CLOTHING BEFORE REUSE.

SECTION IX – ADDITIONAL INGREDIENTS

PRODUCT	INGREDIENT	CAS. NO.	PERCENT (WT)	OCCUPATIONAL EXPOSURE LIMITS	
				TLV	PEL
(0901) DESERT SAND	TITANIUM DIOXIDE DISPERSED COLORANT	13463-67-7 NOT ESTAB	<5 <5	10 MG/M ³ NOT ESTAB	15 MG/M ³ NOT ESTAB
(0902) CAPE COD GRAY	TITANIUM DIOXIDE	13463-67-7	< 5	10 MG/M ³	15 MG/M ³
(0903) CEDARWOOD	TITANIUM DIOXIDE DISPERSED COLORANT	13463-67-7 NOT ESTAB	<5 <5	10 MG/M ³ NOT ESTAB	15 MG/M ³ NOT ESTAB
(0904) RUSTIC BROWN	DISPERSED COLORANT	NOT ESTAB	5	NOT ESTAB	NOT ESTAB
(0907) NATURAL HONEY GOLD TONER	DISPERSED COLORANT	NOT ESTAB	<5	NOT ESTAB	NOT ESTAB
(0908) NATURAL REDWOOD TONER	DISPERSED COLORANT	NOT ESTAB	<5	NOT ESTAB	NOT ESTAB
(0952) REDWOOD	RED IRON OXIDE YELLOW IRON OXIDE BURNT UMBER	1332-37-2 51274-00-1 12713-03-0	<5 <5 <5	5 MG/M ³ (1) 5 MG/M ³ (1) 5 MG/M ³	10 MG/M ³ (1) 10 MG/M ³ (1) 10 PPM
(0953) LIGHT TINT BASE	TITANIUM DIOXIDE	13463-67-7	<5	10 MG/M ³	15MG/M ³
(0954) DARK TINT BASE		SEE SECTION II			

(1) = TIME WEIGHTED AVERAGE

SECTION X – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.