



PRODUCT DATA SHEET

ZAR® EXTERIOR CLEAR POLYURETHANE FINISHES

DESCRIPTION

ZAR Exterior Polyurethanes contain ultraviolet radiation absorbers and antioxidants. They are ideal finishes for bright work and other marine surfaces, exterior doors, natural wood siding, patio furniture, fences, gables and other wood surfaces exposed to harsh extremes of weather.

ZAR EXTERIOR GLOSS & SATIN

- Polyurethane Clear Wood Finish outperforms other exterior clear finishes 2 to 1. ZAR Exterior Polyurethane Clear Wood Finish contains ultraviolet radiation absorbers and antioxidants to minimize the damaging effect of sun and weathering. It is the ideal finish for marine surfaces, exterior doors, natural wood siding, patio furniture, fences, gables and other wood surfaces exposed to harsh extremes of weather. Not for use on decks. Covers 500 to 600 square feet per gallon and is available in pints, quarts, gallons and 11 oz. spray cans.

SURFACE PREP

Stained Steel Doors and Fiberglass Doors: DO NOT SAND. Wood Stain must be thoroughly dry. Do not apply over shellac, lacquer, paint or finishes containing sterates.

New/Bare Wood: Sand smooth using fine sand paper in the direction of the grain. If wood is rough, sand with medium grit sandpaper and finish with fine grit. Remove sanding dust with a tack rag or cloth dampened with paint thinner or mineral spirits.

Old Finishes in Good Condition:

Remove grease, dirt and wax. Sand lightly in the direction of the grain to remove any gloss. Remove sanding dust with a tack rag or cloth dampened with paint thinner or mineral spirits.

Old Finishes in Poor Condition:

Remove completely. All finishes or stains containing wax or water repellents must be removed. Remove sanding dust with a tack rag or cloth dampened with paint thinner or mineral spirits.

APPLICATION

Stir ZAR Satin Exterior Polyurethane thoroughly before and during application. Stirring is not required for ZAR Gloss Exterior Polyurethane Finish. Do not shake! Apply straight from the can. Use a clean natural bristle brush. Dip the brush in the can and let excess drip off.

Flow ZAR on. Avoid over brushing which may trap air bubbles in the finish and result in streaks. Apply thin coats. For best results, apply when air and surface temperatures are above 50°F. Avoid applying in direct sunlight or within one hour of dusk as dew will dull finish

COVERAGE

500 - 600 sq. ft. per gallon.

CLEAN-UP

Clean brushes and tools using UGL® Fastrip® Brush Cleaner, paint thinner or mineral spirits.

CAUTION

Use only in adequate ventilation. Keep out of reach of children.

ZAR® EXTERIOR CLEAR POLYURETHANE FINISHES

DESCRIPTION

ZAR WATER-BASED EXTERIOR POLYURETHANE - A rich amber colored, environmentally safe, clear wood finish specially formulated to protect and beautify exterior wood surfaces exposed to direct sunlight. Containing ultraviolet radiation absorbers and antioxidants, ZAR is the ultimate in exterior protection. ZAR's full-bodied formula brushes on like a conventional polyurethane for maximum durability and beauty. Ideal for wooden marine surfaces (above waterline), exterior doors - including fiberglass and steel doors, natural wood siding, patio furniture, fences, gables and other wood surfaces exposed to direct sunlight and the harsh extremes of weather. Specially formulated for exposure to sunlight. Not for use on decks.

SURFACE PREP

Stained Steel Doors and Fiberglass Doors: Wood Stain must be thoroughly dry. Do not sand uncoated stained surface.

New Wood: Sand smooth using fine sandpaper, vacuum sanding dust. Do not use steel wool. If open grained woods are to be filled, use a filler that does not contain stearates or waxes.

Old Finishes in Good Condition: Remove grease, dirt and wax. Sand lightly in the direction of the grain to remove any gloss. Do not use steel wool. Vacuum all sanding dust. **Old Finishes in Poor Condition, Lacquer, Shellac or Paint:** Remove completely. If the old Finish contains wax or stearates, regardless of condition, remove completely. Do not use steel wool. Sand and vacuum all sanding dust.

APPLICATION

Stir ZAR Satin Water-Based Exterior Polyurethane thoroughly before and during application. Stirring is not required for ZAR Gloss Water-Based Exterior Polyurethane finish. Do not shake! Apply straight from the can. Thinning not required. Apply only when air and surface temperature is between 60°F and the relative humidity is less than 50%. Use a foam brush or synthetic fiber brush. Do not use a roller. Flow ZAR on in the direction of the grain. Do not over brush or trap air bubbles in the finish.

COVERAGE

500 - 600 sq. ft. per gallon.

CLEAN-UP

Clean brushes and tools immediately after use in warm soapy water.

CAUTION

Do not take internally
Close container after use
Keep out of reach of children
Keep from freezing

ZAR FINISHES SELECTOR

	OUTDOOR USE	INDOOR USE	USED ON FLOORS	HOW TO APPLY	APPEARANCE OF FINISH
Exterior Oil Polyurethane	Yes	No	No	Brush	High-Gloss or Satin
Exterior Water Polyurethane	Yes	No	No	Brush	Gloss or Satin

LR 5/03



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com